

– LPI 101 –

Configure Fundamental BIOS Settings

[3]

(Linux Professional Institute Certification)

a

```
.~.  
/V\    by: Andrew Eager  
//  \\  
@.__.@
```

\$Id: gl1.101.1.slides.tex,v 1.4 2003/05/30 04:56:33 waratah Exp \$

^aCopyright © 2002 Andrew Eager, Geoffrey Robertson. Permission is granted to make and distribute verbatim copies or modified versions of this document provided that this copyright notice and this permission notice are preserved on all copies under the terms of the GNU General Public License as published by the Free Software Foundation—either version 2 of the License or (at your option) any later version.

Configure BIOS Fundamental Settings [3]

Objective

Candidates should be able to configure fundamental system hardware by making the correct settings in the system BIOS. This objective includes a proper understanding of BIOS configuration issues such as the use of LBA on IDE hard disks larger than 1024 cylinders, enabling or disabling integrated peripherals, as well as configuring systems with (or without) external peripherals such as keyboards. It also includes the correct setting for IRQ, DMA and I/O addresses for all BIOS administrated ports and settings for error handling.

Configure Fundamental BIOS Settings [3]

Key files, terms, and utilities

`/proc/ioports`

`/proc/interrupts`

`/proc/dma`

`/proc/pci`

Configure Fundamental BIOS Settings [3]

Resources of interest

Large Disk HOWTO by Andries Brouwer

<http://www.linuxdoc.org/HOWTO/Large-Disk-HOWTO.html>

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation
- Basic main memory test (RAM)

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation
- Basic main memory test (RAM)
- Test the presence of various devices

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation
- Basic main memory test (RAM)
- Test the presence of various devices
- On board peripheral selection

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation
- Basic main memory test (RAM)
- Test the presence of various devices
- On board peripheral selection
- Low level device configuration

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation
- Basic main memory test (RAM)
- Test the presence of various devices
- On board peripheral selection
- Low level device configuration
- Selection of boot devices

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation
- Basic main memory test (RAM)
- Test the presence of various devices
- On board peripheral selection
- Low level device configuration
- Selection of boot devices
- Locating an operating system

The PC Firmware—BIOS

Responsible for bring the hardware to a state at which it is ready to boot an Operating System.

- System reset and initialisation
- Basic main memory test (RAM)
- Test the presence of various devices
- On board peripheral selection
- Low level device configuration
- Selection of boot devices
- Locating an operating system
- The BIOS may have password access enabled

The PC Firmware—BIOS

Accessing BIOS Setup

The various vendors have different ways of entering the BIOS menu system

- Del
- F2
- Fn Setup
- Special Boot Floppy
-

The PC Firmware—BIOS

Boot devices

- Floppy
- CDROM / DVD
- IDE Disk
- SCSI Disk
- Network
- Zip / Jazz
- USB Disk

The PC Firmware—BIOS

Resource Assignment

- PC's have memory mapped I/O and devices must not have overlapping I/O Addresses

The PC Firmware—BIOS

Resource Assignment

- PC's have memory mapped I/O and devices must not have overlapping I/O Addresses
- Devices sharing interrupts such as `ttys0` and `ttys2` must not be used at the same time

The PC Firmware—BIOS

Resource Assignment

- PC's have memory mapped I/O and devices must not have overlapping I/O Addresses
- Devices sharing interrupts such as `ttys0` and `ttys2` must not be used at the same time
- Direct Memory Access (DMA) allows some devices to access memory directly, rather than via the CPU

The PC Firmware—BIOS

Resource Assignment

- PC's have memory mapped I/O and devices must not have overlapping I/O Addresses
- Devices sharing interrupts such as `ttys0` and `ttys2` must not be used at the same time
- Direct Memory Access (DMA) allows some devices to access memory directly, rather than via the CPU
- Some PCI controllers may have to be in a Bus Mastering Slot

The PC Firmware—BIOS

Resource Assignment

- PC's have memory mapped I/O and devices must not have overlapping I/O Addresses
- Devices sharing interrupts such as `ttys0` and `ttys2` must not be used at the same time
- Direct Memory Access (DMA) allows some devices to access memory directly, rather than via the CPU
- Some PCI controllers may have to be in a Bus Mastering Slot
- PCI devices may share a common interrupt

The PC Firmware—BIOS

Common Device Settings

Device	I/O Address	IRQ	DMA
ttyS0	3F8	4	NA
ttyS1	2F8	3	NA
ttyS2	3E8	4	NA
ttyS3	2E8	3	NA
lp0	378-37F	7	NA
lp1	278-27F	5	NA
fd0, fd1	3F0-3F7	6	2
fd2, fd3	370-377	10	3

The PC Firmware—BIOS

1023 Cylinder Limit

- Ten bit addressing of cylinders— $11\ 1111\ 1111_2 = 1023_{10}$

The PC Firmware—BIOS

1023 Cylinder Limit

- Ten bit addressing of cylinders— $11\ 1111\ 1111_2 = 1023_{10}$
- Large Block Addressing (LBA) used for disks larger than 1023 cylinders ($\approx 8\text{Gb}$)

The PC Firmware—BIOS

1023 Cylinder Limit

- Ten bit addressing of cylinders— $11\ 1111\ 1111_2 = 1023_{10}$
- Large Block Addressing (LBA) used for disks larger than 1023 cylinders ($\approx 8\text{Gb}$)
- The boot loader must be below cylinder 1024

The PC Firmware—BIOS

1023 Cylinder Limit

- Ten bit addressing of cylinders— $11\ 1111\ 1111_2 = 1023_{10}$
- Large Block Addressing (LBA) used for disks larger than 1023 cylinders ($\approx 8\text{Gb}$)
- The boot loader must be below cylinder 1024
- Older versions of LILO must have `/boot` (the kernel) entirely below cylinder 1024

The PC Firmware—BIOS

1023 Cylinder Limit

- Ten bit addressing of cylinders— $11\ 1111\ 1111_2 = 1023_{10}$
- Large Block Addressing (LBA) used for disks larger than 1023 cylinders ($\approx 8\text{Gb}$)
- The boot loader must be below cylinder 1024
- Older versions of LILO must have `/boot` (the kernel) entirely below cylinder 1024
- The Grub bootloader does not have these restrictions

Viewing /proc/*

`/proc/dma`

```
$ cat /proc/dma ↵
```

```
4: cascade
```

`/proc/interrupts`

```
$ cat /proc/interrupts ↵
```

```
          CPU0
0:        2623139      XT-PIC  timer
1:         11619      XT-PIC  keyboard
2:           0      XT-PIC  cascade
5:        73992      XT-PIC  Maestro3(i)
8:           1      XT-PIC  rtc
11:        308      XT-PIC  usb-uhci,
Texas Instruments PCI4451 PC card Cardbus Controller,
Texas Instruments PCI4451 PC card Cardbus Controller, eth0
12:        926438      XT-PIC  PS/2 Mouse
14:        504452      XT-PIC  ide0
NMI:           0
ERR:           0
```

/proc/ioprots

```
$ cat /proc/ioprots ↵  
 0000-001f : dma1  
0020-003f : pic1  
0040-005f : timer  
0060-006f : keyboard  
0070-007f : rtc  
0080-008f : dma page reg  
00a0-00bf : pic2  
00c0-00df : dma2  
00f0-00ff : fpu  
01f0-01f7 : ide0  
02f8-02ff : serial(auto)  
0378-037a : parport0  
03c0-03df : vga+
```

`/proc/pci`

```
$ cat /proc/pci ↵
```

```
PCI devices found:
```

```
Bus 0, device 0, function 0:
```

```
Host bridge: Intel Corp. 82815 815 Chipset Host Bridge  
and Memory Controller Hub (rev 2).
```

```
Prefetchable 32 bit memory at 0xe4000000 [0xe7fffffff].
```

```
Bus 0, device 1, function 0:
```

```
PCI bridge: PCI device 8086:1131 (Intel Corp.) (rev 2).
```

```
Master Capable. Latency=32. Min Gnt=12.
```

```
Bus 0, device 30, function 0:
```

```
PCI bridge: Intel Corp. 82820 820 (Camino 2) Chipset  
PCI (-M) (rev 3).
```

```
Master Capable. No bursts. Min Gnt=6.
```

The End